This model MCW002052M53A is a multioctave high power amplifier operating between 20MHz and 520MHz and offering a wide dynamic range with 200W Min saturated power. The employment of Gallium Nitride (GaN) and chip-and-wire technology in manufacturing ensures this module state-of-the-art power performance with excellent power-to-volume ratio. It is ideal for RF systems, Communication, EMC, Test and Measurement applications. This module is equipped with alarmfunctions for over-temperature, over-voltage, over-current, which will shut down automatically under these conditions.

Features:

- Small Size and light weight
- Instantaneous ultra broadband
- 50 Ohms Input and Output matched
- Built-In control and protection circuits

Electrical Specifications (@+28VDC, 25°C, 50Ω)

Parameter	Symbol	Minimum	Typ	Maximum	Units
Operating Frequency	BW	20		520	MHz
RF Output Power @PSAT	PSAT	200			Watt
Power Gain @PSAT	Gp		53		dB
Input Return Loss	S11			-10	dB
Harmonics @150W	H		-10		dBc
Spurious Signals @PSAT	Spur		-60		dBc
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC	30	32	34	Volt
DC Current @200W	IDD		18		Amp

Absolute Maximum Rating

Parameter	Rating	
Input RF drive level without damage	+10 dBm	Maximum
Load VSWR @ POUT =100W	∞ @ all load phase & amplitude for duration of 1 minute; 3:1 @ all load phase & amplitude continuous	
Over Temperature	85°C shutdown	

Environmental Specifications (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Storage Temperature	-25		65	°C	
Relative Humidity（non-condensing）			95	%	

Mechanical Specifications

Parameter	Value	Units	Notes
Dimensions	200x150x30 [7.5x5.9x1.2]	mm [inch]	Maximum
Weight	2[4]	kg [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	N-Typ, Female		
DC Interface Connector	Hybird,D-Sub 7-Pin, Male		
Cooling	Extemal Heatsink (Not Supplied)		If need can add

DC Interface Connector

Pin #	Description	Specifications
A1	VDD	28VCC
A2	GND	Ground
1	ENABLE	Amplifier Enable: TTL Logic High (3.3V) (Internally Pulled-Low)
2	CURRENT	Analog voltage relative to IDD @ 100mV per Ampere
3	TEMP MONITOR	Analog voltage relative to Module's Temperature @ 10 mV/°C
4	GND	Ground
5	NC	No electrical connection

Outline Drawing (All dimensions in mm [inch])

